



T430

Rated power: 500 W
Forward thrust: 8 kg
Backward thrust: 8 kg



Technical parameters

Rated speed	2700r/min	Sealing form	Leakless,magneically coupled
Rated voltage	48VDC/65VDC/80VDC/100VDC/130VDC 150VDC/200VDC/250VDC/300VDC	Depth rating	0-850/0-1500/0-3000/0-6000/Full ocean depth,Service depth>1500m,Oil filled seal
Housing	Aluminum alloy / Titanium alloy	Electronics	Built in (0-1500m) / External
Rotation direction	Left-handed / Right-handed rotation	Signal power	12VDC(±5%),≤250mA
Material of propeller	Stainless steel	Nozzle	Black
Temperature	Storage temperature: -40~70℃, Service temperature: -5~40℃	Control mode/ Speed feedback	Analog voltage (pulse feedback/analog voltage feedback) / PPM / RS485 / CAN



Parameters for model selection

Working water depth	External dimensions (mm)	Length (mm)	weight in the air (kg)	Underwater weight (kg)	Connector model	Optional voltage level
0-850 & 0-1500	φ135.1	215~264	1.7~2.1	1.2~1.5	MCBH8M	48~300VDC
0-3000 & 0-6000	φ135.1	214~251	1.3~1.6	1.3~1.6	MCPBOF8M	Outer diameter of oil pipe3/4" oil pipe outer diameter3"
Full ocean depth	φ135.1	214~251	1.3~1.6	1.3~1.6	PBOF8M	

Note: The weight change of oil-filled compensation products is affected by the length of the oil pipe. For details, please consult technical personnel.

Thrust curve

