

T2020

Rated power: 6.5 kW

Forward thrust: 120 kg

Backward thrust: 60 kg




Technical parameters

Rated speed	1600r/min	Sealing form	Leakless,magneically coupled
Rated voltage	260VDC/300VDC/330VDC/600VDC	Depth rating	0-850/0-1500/0-3000/0-6000/Full ocean depth,Service depth>850m,Oil filled seal
Motor compartment	Aluminum alloy / Titanium alloy	Electronics	Built in (0-1500m) / External
Rotation direction	Left-handed / Right-handed rotation	Signal power	12VDC(±5%)
Material of propeller	Stainless steel	Nozzle	Black
Temperature	Storage temperature: -40~70℃, Service temperature: -5~40℃	Control mode/ Speed feedback	Analog voltage (pulse feedback/analog voltage feedback) / PPM / RS485 / CAN

Propeller external dimensions



Unit: mm



Working water depth: 0-850m

Driver external dimensions

Unit: mm



Working water depth: 0-3000m


Parameters for model selection

Working water depth	External dimensions (mm)	Length (mm)	weight in the air (kg)	Underwater weight (kg)	Connector model	Optional voltage level
0-850 & 0-1500	φ322.8	422~533	12.9~16.3	8.6~10.4	MCBH12M	260~600VDC
0-3000 & 0-6000	φ322.8	390.4	14.3~15.1	9.3~10.1	MCPBOF8M	Outer diameter of oil pipe3/4" oil pipe outer diameter3"
Full ocean depth	φ322.8	390.4	14.3~15.1	9.3~10.1	PBOF8M	

Note: The weight change of oil-filled compensation products is affected by the length of the oil pipe. For details, please consult technical personnel.

Thrust curve

Thrust vs Propeller RPM table1



Thrust vs Input power table 2

